

Professionally engineered slab over 592 ft²

Accessory Building Specifications- Part 1

Development Permit #	 		
Civic or Rural Address:			
		Pre-manufact	- ROOF les 3/8" OSB roof sheathing ured engineered trusses at 24" s per manufacturer's
Check with your Municipality's height restrictions Slab or property of the stamped s	s up to 592 ft² require a 4" concrete pressure treated mud sill slab foundations over 592 ft² must submit engineered plans crete to be air entrained and 32 MPa or	Vinyl siding or stucco building paper 3/8" OSB wall sheathing 2X4 at 16" or 24"o.c.	EAVES 16" maximum when less than 750mm side yard. CLEARANCE 8" minimum clearance to untreated wood
Roofing Material Asphalt Shingles Cedar, Pine Shakes/Shingles Metal Roofing Other (specify)	Interior Development NOTE: A separate permit is required for each of these items (if applicable) ☐ Electrical ☐ Gas ☐ Plumbing ☐ Other (specify):	Please Note: Windows cannot be placed in a wall that is closer than 4 feet to a neighbour's property.	
Roofing Sheathing ☐ Min. 3/8" OSB or plywood NOTE: OSB or plywood less than ½" requires H clips and bridge blocking ☐ ½" OSB or plywood ☐ Other (specify)	Wall Sheathing ☐ 3/8" OSB ☐ 3/8" plywood ☐ 1/2" plywood ☐ 1/2" OSB	If the roof framing roof loading to the door beam, please the garage door bean Garage door beal loading must be minin c/w a minimum of 3" b	overhead garage specify the size of n. ms without roof num size 2 – 2 x 12
Roof Framing ☐ Pre-manufactured Engineered Truss ☐ Stick Build Rafters (provide details)	☐ Other (specify):	Walls to be secu 12.7mm anchor bolts maximum.	at 2.4m on center
Exterior Finish ☐ Vinyl Siding ☐ Stucco ☐ Metal Siding	☐ 2 x 6 @ 16/24" o.c. ☐ Insulated walls and ceilings ☐ Garage Door Beam	line.	ii unuergiounu gas
Other (specify) Foundation 4" Slab Pressure treated mud sill	Length:# of Plys: Depth:# of Plys: Built Up	Direction of Trus ☐ Trusses parallel door opening ☐ Trusses perperoverhead door open	to overhead
☐ Strip footing & 4' frost wall			

Accessory Building Specifications- Part 2

